HUBBELL
Wiring Device-Kellems

Locking Devices, Twist-Lock®, Industrial, 2-Gang Surface Mount Reccle, 20A 250V, 2-Pole 3-Wire Grounding, L6-20R, Screw Terminal, Gray

By Hubbell Wiring Device-Kellems
Catalog # HBL2320SR2

Locking Devices, Twist-Lock®, Industrial, 2-Gang Surface Mount Reccle, 20A 250V, 2-Pole 3-Wire Grounding, L6-20R, Screw Terminal, Gray

Features

- Accepts Hubbell shrouded and standard NEMA locking plugs
- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Catalog number and color coded voltage rating are visible even when in use
- Engineered thermoplastic housing is impact and corrosion resistant, making it suitable for heavy-duty industrial environments

Application

Heavy Duty Industrial Shrouded

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L6-20R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Configuration

Number of Gang(s)	2-Gang

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC
Connectivity	Back Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	5.12 in
Display Size	Standard Sized Product
Weight	0.55 lb.
Height	2.22 in
Width	5.12 in
Dimensions	5.12 in x 5.12 in x 2.22 in

General

Specifications	• Body Contact Carrier - Natural (white) nylon • Body Holding Screws - Steel, zinc plated • Contacts - Brass • Housing / Flange - Gray RPT • Terminal Retainer - Clear polycarbonate
UPC	783585234120
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Receptacles
Material	Thermoplastic

Logistics

Carton Quantity	5

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [Spanish, French, English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved