**HUBBELL**
**Wiring Device-Kellems**

# Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 20A 3-Phase WYE 277/480V AC, 4-Pole 4-Wire Non-Grounding, L19-20R, Screw Terminal

By Hubbell Wiring Device-Kellems
Catalog # HBL2456

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 20A 3-Phase WYE 277/480V AC, 4-Pole 4-Wire Non- Grounding, L19-20R, Screw Terminal, White

## Features

- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

## Application

Insulgrip

## Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Environmental - Terminal Identification - Terminals identified in accordance with UL 498, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only.

## Specifications

| | |
|---|---|
| Standards - RoHS Compliance Status | CM |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| EU RoHS Indicator | Yes |
| Nema Rating | L19-20R |
| Industry Standard(s) | • Certified to CSA C22.2 No.42<br>• Fed.Spec. W-C-596<br>• Listed to UL 498 |

## Conductor

| | |
|---|---|
| Number Of Wires | 4-Wire |
| Wire Size | #16 AWG to #8 AWG |
| Number Of Poles | 4-Pole |

## Current

| | |
|---|---|
| Amperage Rating | 20 A |
| Voltage Rating Description | 3 Phase WYE 277/480 VAC |
| Dielectric Strength | Withstands 2,000V minimum |
| Current Rating | 20 A |
| Voltage Rating | 3 Phase WYE 277/480 VAC |
| Connectivity | Back Wired Screw Terminals |
| Phase | 3 Phase WYE |
| Current / Amperage Rating | 20 A |

## Dimensions

| | |
|---|---|
| Length | 3.06 in |
| Display Size | Standard Sized Product |
| Weight | 0.4 lb. |
| Height | 2.27 in |
| Width | 3.06 in |
| Dimensions | 3.06 in x 3.06 in x 2.27 in |

## General

| | |
|---|---|
| Specifications | • Assembly Screws - Steel - nickel plated<br>• Contacts - Brass<br>• Housing - Nylon<br>• Mounting Screw - Nickel plated brass<br>• Terminal Clamp - Cold rolled steel – nickel plated<br>• Terminal Retainer - Clear polycarbonate<br>• Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson) |
| UPC | 783585038421 |
| Type | Flanged Receptacle |
| Material - Mounting Hardware | Screw Mounting |
| Item Type | 20A Insulgrip® Flanged Receptacle |
| Material | Nylon |

## Logistics

| | |
|---|---|
| Carton Quantity | 10 |

## Operational

| | |
|---|---|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |

| | |
|---|---|
| Horsepower - Maximum | 5 |

## Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [French, English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved