**HUBBELL**
**Wiring Device-Kellems**

# Locking Devices, Twist-Lock®, Safety Shroud, Angled Receptacle, 20A 3 -Phase Wye 120/208V AC, 4-Pole 5-Wire Grounding, L21-20R, Screw Terminal, Gray

By Hubbell Wiring Device-Kellems
Catalog # HBL2510AR

Locking Devices, Twist-Lock®, Safety Shroud, Angled Receptacle, 20A 3 -Phase Wye 120/208V AC, 4-Pole 5-Wire Grounding, L21-20R, Screw Terminal, Gray

## Features

- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Catalog number and color coded voltage rating are visible even when in use
- Engineered thermoplastic housing is impact and corrosion resistant, making it suitable for heavy-duty industrial environments

## Application

Heavy Duty Industrial Shrouded

## Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

## Specifications

| | |
|---|---|
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| EU RoHS Indicator | Yes |
| Nema Rating | L21-20R |
| Industry Standard(s) | • Certified to CSA C22.2 No.42<br>• Fed.Spec. W-C-596<br>• Listed to UL 498 |

## Conductor

| | |
|---|---|
| Number Of Wires | 5-Wire |
| Wire Size | #16 AWG to #8 AWG |
| Number Of Poles | 4-Pole |

## Configuration

| | |
|---|---|
| Number of Gang(s) | 1-Gang |

## Current

| | |
|---|---|
| Amperage Rating | 20 A |
| Voltage Rating Description | 3 Phase WYE 120/208 VAC |
| Dielectric Strength | Withstands 2,000V minimum |
| Current Rating | 20 A |
| Voltage Rating | 3 Phase WYE 120/208 VAC |
| Connectivity | Back Wired Screw Terminals |
| Phase | 3 Phase WYE |
| Current / Amperage Rating | 20 A |

## Dimensions

| | |
|---|---|
| Length | 4.77 in |
| Display Size | Standard Sized Product |
| Weight | 0.75 lb. |
| Height | 3.14 in |
| Width | 2.85 in |
| Dimensions | 4.77 in x 2.85 in x 3.14 in |

## General

| | |
|---|---|
| Specifications | • Body Contact Carrier - Natural (white) nylon<br>• Body Holding Screws - Steel, zinc plated<br>• Contacts - Brass<br>• Housing / Flange - Gray RPT<br>• Mounting Plate - Steel, zinc plated<br>• Terminal Retainer - Clear polycarbonate |
| UPC | 783585234960 |
| Type | Angled Receptacle |
| Material - Mounting Hardware | Screw Mounting |
| Item Type | 20A Safety-Shroud® Receptacle |
| Material | Valox™ |

## Logistics

| | |
|---|---|
| Carton Quantity | 10 |

## Operational

| | |
|---|---|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Horsepower - Maximum | 2 |

## Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [Spanish, French, English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved