

HUBBELL
Wiring Device-Kellems

Locking Devices, Twist-Lock®, Insulgrip® Inlet, 30A, 125V AC, 2 Pole 3 Wire, NEMA L5-30P

By Hubbell Wiring Device-Kellems

Catalog # [HBL2615M3](#)

Locking Devices, Twist-Lock®, Insulgrip® Inlet, 30A, 125V AC, 2 Pole 3 Wire, NEMA L5-30P, Back Wired, Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover.



Features

- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Extra Heavy Duty Industrial

Performance

Electrical-Current Interrupting - Certified at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Mechanical - Terminal Accommodation - #16 - #8 AWG stranded, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Environmental Conditions	Weather Protective
EU RoHS Indicator	Yes
Nema Rating	L5-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	125 VAC
Connectivity	Back Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Color	Gray
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Cover Assembly - Cast Aluminum with powder coat paint • Housing / Flange - Nylon • Mounting Screw - Stainless Steel • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson) • UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
Listings	783585039954
UPC	Screw Mounting
Material - Mounting Hardware	Insulated Body
Insulation	30A Insulgrip® Flanged Inlet
Item Type	Nylon
Material	

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French\]](#)

