

Locking Devices, Twist-Lock®, Safety-Shroud® Receptacle, 30A, 250V AC, 2 Pole, 3 Wire Grounding, NEMA L6-30R, PBT housing, semi-flush, Two Gang, Gray

By Hubbell Wiring Device-Kellems
Catalog # [HBL2620SR2](#)

Locking Devices, Twist-Lock®, Safety-Shroud® Receptacle, 30A, 250V AC, 2 Pole, 3 Wire Grounding, NEMA L6-30R, PBT housing, semi-flush, Two Gang, Gray

Features

- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Catalog number and color coded voltage rating are visible even when in use
- Engineered thermoplastic housing is impact and corrosion resistant, making it suitable for heavy-duty industrial environments

Application

Heavy Duty Industrial Shrouded

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L6-30R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Configuration



Number of Gang(s)	2-Gang
Current	
Amperage Rating	30 A
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	250 VAC
Connectivity	Back Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	30 A
Dimensions	
Length	5.12 in
Display Size	Standard Sized Product
Weight	0.55 lb.
Height	2.22 in
Width	5.12 in
Dimensions	5.12 in x 5.12 in x 2.22 in
General	
Color	Gray, White
Specifications	• Body Contact Carrier - Natural (white) nylon • Body Holding Screws - Steel, zinc plated • Contacts - Brass • Housing / Flange - Gray RPT • Terminal Retainer - Clear polycarbonate
Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
UPC	783585234366
Material - Mounting Hardware	Screw Mounting
Item Type	30A Safety-Shroud® Receptacle
Material	Valox™
Logistics	
Carton Quantity	5

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [Spanish, French, English]



A Hubbell brand