

Locking Devices, Twist-Lock®, Insulgrip®
Flanged Inlet, 30A, 250V AC, 2 Pole, 3 Wire
Grounding, NEMA L6-30P, Heat stabilized,
gray nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2625F](#)

Locking Devices, Twist-Lock®, Insulgrip® Flanged Inlet, 30A, 250V
AC, 2 Pole, 3 Wire Grounding, NEMA L6-30P, Heat stabilized,
gray nylon

Features

- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L6-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum



Current Rating	30 A
Voltage Rating	250 VAC
Connectivity	Back Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Length	2.88 in
Display Size	Standard Sized Product
Weight	0.20 lb.
Height	2.16 in
Width	2.88 in
Dimensions	2.88 in x 2.88 in x 2.16 in

General

Color	Gray
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Housing / Flange - Nylon • Mounting Screw - Nickel plated brass • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
UPC	783585038919
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	30A Insulgrip® Flanged Inlet
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[French\]](#)



A Hubbell brand