HUBBELL
Wiring Device-Kellems

Locking Devices, Hubbellock, Industrial, Flanged Inlet, 60A 600V AC, 4-Pole 5-Wire Grounding, Non NEMA, Screw Terminal, Blue

By Hubbell Wiring Device-Kellems
Catalog # HBL26522

Locking Devices, Hubbellock, Industrial, Flanged Inlet, 60A 600V AC , 4-Pole 5-Wire Grounding, Non NEMA, Screw Terminal, Blue

Features

- Molded-in male contacts are resistant to damage and provide a consistently positive connection
- Color coded metallic housing enhances safety and abuse resistance
- Box terminals in conjunction with stainless steel terminal screws provide maximum termination strength and dependability

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - UL 94 V0, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #8 AWG - #4 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA Standard • Listed to UL Standard

Conductor

Number Of Wires	5-Wire
Wire Size	#8 AWG to #4 AWG
Number Of Poles	4-Pole

Current

Amperage Rating	60 A
Voltage Rating Description	600 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	60 A
Voltage Rating	600 VAC
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	60 A

Dimensions

Length	3.95 in
Display Size	Standard Sized Product
Weight	1.75 lb.
Height	4.12 in
Width	4.12 in
Dimensions	3.95 in x 4.12 in x 4.12 in

General

Color	Blue
Specifications	• Contacts - Brass • Flanged Housing - Zinc plated steel • Inlet Interior - Phenolic • Terminal - Copper • Terminal Screws - Stainless Steel
UPC	783585017624
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	60A Grounding Hubbellock® Flanged Inlet
Material	Steel, Zinc Plated

Logistics

Carton Quantity	5

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved