

Locking Devices, Twist-Lock®, Insulgrip® Plug, 30A, 125/250V AC, 3 Pole, 3 Wire Non-Grounding, NEMA L10-30P, Black and white nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2661](#)

Locking Devices, Twist-Lock®, Insulgrip® Plug, 30A, 125/250V AC, 3 Pole, 3 Wire Non-Grounding, NEMA L10-30P, Black and white nylon

Features

- Superior cord grip design protects terminations from excess strain
- Clear, funnel shaped wire entry for ease of termination
- Integral dust shield protects wiring chamber from dust or contaminants

Application

Extra Heavy Duty Industrial

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L10-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire Non-Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	30 A
-----------------	------



Voltage Rating Description	125/250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	125/250 VAC
Phase	Single Phase
Current / Amperage Rating	30 A

General

Color	Black, White
Cord Range	0.300"-0.950" (7.6-24.1)
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Housing / Triple Gripper - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson) • UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42

Listings

UPC	783585456782
Item Type	30A Insulgrip® Plug
Material	Nylon

Logistics

Carton Quantity	30
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)