

Locking Devices, Twist-Lock®, Watertight
Safety-Shroud® Reverse Service Plug, 30A,
3 Phase 250V AC, 3 Pole, 4 Wire
Grounding PBT housing PBT clamps

By Hubbell Wiring Device-Kellems
Catalog # [HBL2723SR](#)

Locking Devices, Twist-Lock®, Watertight Safety-Shroud® Reverse
Service Plug, 30A, 3 Phase 250V AC, 3 Pole, 4 Wire Grounding,
Black PBT housing, white PBT clamps

Features

- UL Type 4X Environmental seal protects connection while in use
- One-piece, engineered thermoplastic housing is impact-resistant for heavy-duty industrial environments
- Superior cord grip design protects terminations from excess strain

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - V0 per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - Type 4, 4X, 12, IP66 suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Nema Rating	L15-30
Standards - RoHS Compliance	CM
Status	
Industry Standard(s)	UL Listed, CSA Certified To Type 4, 4X And Type 12

Conductor

Number Of Poles	3-Pole
Number Of Wires	4-Wire
Wire Size	#16 AWG to #8 AWG

Current

Amperage Rating	30 A
Voltage Rating	250 VAC
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current / Amperage Rating	30 A
Current Rating	30 A



Dimensions

Height	5.51 in
Width	2.95 in
Length	2.95 in
Dimensions	2.95 in x 2.95 in x 5.51 in

General

Specifications	• Contacts - Brass • Housing - PBT • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42 • UL Listed • CSA Certified to Type 4, 4X and Type 12
UPC	783585355535
Type	Reverse Service Plug
Item Type	30A Watertight Safety-Shroud® Reverse Service Plug

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	3

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)