

Locking Devices, Twist-Lock®, Marine Grade, Male Plug, 30A 3-Phase 120/208V AC, 4-Pole 5-Wire Grounding, L21-30P, Screw Terminal, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL28CM11](#)

Locking Devices, Twist-Lock®, Marine Grade, Male Plug, 30A 3-Phase 120/208V AC, 4-Pole 5-Wire Grounding, L21-30P, Screw Terminal, Yellow

Features

- Nickel plated blades and stainless steel screws provide maximum corrosion resistance
- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Integral dust shield protects wiring chamber from dust or contaminants

Application

Heavy Duty Industrial/Marine

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 - #8 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Environmental Conditions	Corrosion Resistant
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L21-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	5-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	4-Pole

Configuration

Cord Type	All Listed Portables
-----------	----------------------



Current

Amperage Rating	30 A
Voltage Rating Description	120/208 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	120/208 VAC
Connectivity	Pressure Terminal Screws
Phase	3 Phase WYE
Current / Amperage Rating	30 A

Dimensions

Length	2.33 in
Display Size	Standard Sized
Weight	0.25 lb.
Height	2.75 in
Width	2.33 in
Dimensions	2.33 in x 2.33 in x 2.75 in

General

Color	Yellow
Cord Range	0.350"-1.150" (9-29)
Specifications	• Assembly Screws - Stainless Steel • Blades - Nickel Plated Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Bronze (Phillips / Slotted / Robertson) • UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42

Listings

UPC	783585039770
Material - Mounting Hardware	Cord Mounted
Item Type	30A Corrosion Resistant Insulgrip® Plug
Material	Nylon

Logistics

Carton Quantity 10

Horsepower - Maximum 3

Operational

Operating Temperature Maximum continuous 75°C and minimum -40°C without impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French, English\]](#)



A Hubbell brand