HUBBELL
Wiring Device-Kellems

Watertight Devices, Twist-Lock® Plug, 30A, 3 Phase WYE 277/480V AC, 4 Pole, 5 Wire, Thermoplastic elastomer, NEMA L22-30P, Yellow

By Hubbell Wiring Device-Kellems
Catalog # HBL28W82

Watertight Twist-Lock® Plug, 30A

Features

- Smooth body design minimizes collection points simplifying the wash down process
- Strain relief nut always seals on the body, minimizing debris collection
- Stainless steel hardware and corrosion-resistant connection points

Performance

Electrical - Current Interrupting - Rated for current interruption per UL498, Electrical - Dielectric Voltage - 2500V AC, Electrical - Max Working Voltage - As marked, Electrical - Temperature Rise - 30°C max per UL498 at rated current, Environmental - UV resistance - All exposed materials are UV stabilized, Environmental - Moisture Resistance - UL Listed 4, 4X, 12, 6, 6P, Environmental - Operating Temperatures - -40°C (without impact) to +60°C continuous, Mechanical - Cord Accommodation - 0.375"-1.000" (9.5-25.4)

Specifications

EU RoHS Indicator	Contact Manufacturer
Nema Rating	L22-30P
Industry Standard(s)	Meets NEMA WD-1, WD-6 And ANSI Standards

Conductor

Number Of Wires	5-Wire
Wire Size	• Min Cords: 12/3 SJ, 16/3 S, 14/4 SJ, 18/4 S, 18/5 S • Max Cord: 8/3 S, 8/4 S, 10/5 S
Number Of Poles	4-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	3-Phase Y 277/480 VAC
Voltage Rating	3-Phase Y 277/480 VAC
Current / Amperage Rating	30 A

Dimensions

Length	2.77 in
Height	3.94 in
Width	2.77 in
Dimensions	2.77 in x 2.77 in x 3.94 in

General

Color	Yellow
UPC	783585131771
Type	Plugs
Item Type	30A Watertight Twist-Lock® Plug

Logistics

Carton Quantity	10

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved