

Locking Devices, Twist-Lock®, VariLoad,
Male Plug, 30A 250V DC/600V AC, 4-Pole
5-Wire Grounding, Non-NEMA, Screw
Terminal, Black, Unique Center Pin

By Hubbell Wiring Device-Kellems
Catalog # [HBL45315](#)

Locking Devices, Twist-Lock®, VariLoad, Male Plug, 30A 250V
DC/600V AC, 4-Pole 5-Wire Grounding, Non-NEMA, Screw
Terminal, Black, Unique Center Pin

Features

- Heat resistant thermoset construction

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - HB
or better per UL 94 or CSA 22.2 No. 0.6, Environmental -
Operating Temperatures - Maximum Continuous 75°C Minimum
-40°C (w/o impact), Mechanical - Terminal Accommodation - #14
AWG - #10 AWG stranded copper wire only., Mechanical -
Terminal Identification - Terminals identified in accordance with
UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	Non-NEMA
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	5-Wire Grounding
Wire Size	#14 AWG to #10 AWG
Number Of Poles	4-Pole

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current

Amperage Rating	30 A
Voltage Rating Description	250 VDC/600 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A



Voltage Rating	250 VDC/600 VAC
Connectivity	Screw Terminals
Phase	Multi Phase
Current / Amperage Rating	30 A

Dimensions

Length	2.77 in
Display Size	Standard Sized
Weight	0.35 lb.
Height	2.13 in
Width	2.13 in
Dimensions	2.77 in x 2.13 in x 2.13 in

General

Color	Black
Cord Range	0.625"-1.00"
Specifications	• Assembly Screws - Brass • Blades - Brass • Cord Clamp - Zinc Plated Steel • Cover - Molded thermoset • Housing - Molded Thermoset • Terminal Screw - Brass
UPC	783585236575
Material - Mounting Hardware	Cord Mounted
Item Type	30A Variload® Plug
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	---

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)