

Locking Devices, Twist-Lock®, Valise,
Female Connector Body, 15A 250V, 2-Pole
3-Wire Grounding, L6-15R, Screw Terminal,
Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL4579VY](#)

Twist-Lock® Valise® Female Connector Body 15A

Features

- Two captive multiple drive assembly screws
- Totally insulated impact and crush resistant nylon body
- Powerful cord grips prevent conductor slippage and strain on wiring terminals

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for full rated current,
Electrical - Dielectric Voltage - Withstand 2,000V minimum,
Environmental - Flammability - HB or better per UL 94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20
Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Environmental - Terminal Identification - Terminals identified in accordance with UL 498, Mechanical - Terminal Accommodation - #18 AWG - #12 AWG stranded copper wire only.

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L6-15R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #12 AWG
Number Of Poles	2-Pole
Cable Range	0.220 - 0.660 in

Current

Amperage Rating	15 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A



Voltage Rating	250 VAC
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	15 A

Dimensions

Length	1.50 in
Display Size	Standard
Weight	0.20 lb.
Height	2.59 in
Width	1.50 in
Dimensions	1.50 in x 1.50 in x 2.59 in

General

Color	Yellow
Cord Range	0.220"-0.660"(5.6-16.8)
Specifications	• Assembly Screws - Steel - Zinc plated • Blades - Brass • Cable Inserts - Polyphenylene Oxide • Housing - Nylon • Terminal Clamp - Cold rolled steel – nickel plated • Terminal Screws - #6-32 Brass (Phillips / Slotted / Robertson)
UPC	783585236674
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	15A Valise® Connector
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand