

Locking Devices, Twist-Lock®, Industrial, Male Plug, 15A 125V, 2-Pole 3-Wire Grounding, L5-15P, Screw Terminal, Black and White, Angled,

By Hubbell Wiring Device-Kellems
Catalog # [HBL4720CA](#)

Locking Devices, Twist-Lock®, Industrial, Male Plug, 15A 125V, 2-Pole 3-Wire Grounding, L5-15P, Screw Terminal, Black and White, Angled,

Features

- Individually molded face for each blade configuration
- Roomy wiring chamber provides ample space for wiring
- Ribbed nylon housing provides a secure grip that's impact and chemical resistant

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L5-15P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole
Cable Range	0.325 - 0.655 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------



Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	2.08 in
Display Size	Standard Sized
Weight	0.15 lb.
Height	1.21 in
Width	1.52 in
Dimensions	2.08 in x 1.52 in x 1.21 in

General

Color	Black, White
Cord Range	0.325"-0.655"(8.3-16.6)
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #8-32 Brass (Phillips / Slotted / Robertson)
UPC	783585171203
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	15A Grounding Insulgrip® Plug
Material	Nylon

Logistics

Pallet Quantity	4500
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French, English\]](#)



A Hubbell brand