

Twist-Lock®, Industrial, Combo Face Duplex
Receptacle, 15A 125V, 2-Pole 3-Wire
Grounding, 5-15R and L5-15R, Screw
Terminal, Brown, 1) Feed 1) Return

By Hubbell Wiring Device-Kellems
Catalog # [HBL4792](#)

Twist-Lock® Industrial Combination Face Duplex Receptacle 15A,
1-Feed 1-Return

Features

- Industrial
- Combo Face Duplex Receptacle
- 15A 125V
- 2-Pole 3-Wire Grounding

Application

Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-2 or better, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-15R, L5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • UL Listed to UL498 File E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	15 A
Voltage Rating	125 V
Connectivity	Back and Side Wired
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.3 lb.
Height	0.88 in
Width	1.5 in
Dimensions	3.28 in x 1.5 in x 0.88 in

General

Color	Brown
Style	Finder Groove Face
Series	Special Combination Receptacle
Specifications	• Base - Reinforced thermoplastic polyester • Face - Reinforced thermoplastic polyester • Power Contacts - .032" (.81) Brass
UPC	783585236995
Type	Duplex Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Combination Duplex Receptacles

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand