

HUBBELL
Wiring Device-Kellems

Locking Devices, Twist-Lock®, Marine Grade, Flanged Receptacle, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screw Terminal, Stainless Steel

By Hubbell Wiring Device-Kellems
Catalog # [HBL47CM15](#)

Locking Devices, Twist-Lock®, Marine Grade, Flanged Receptacle,
15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screw Terminal,
Stainless Steel



Features

- Heat resistant thermoset construction
- Stainless steel casing
- #8-32 terminal screws
- Mounting screws included

Application

Marine Wiring Devices

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #18 - #10 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L5-15R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed. Spec. W-C-596 • Listed to UL 498 • WR Rating

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 VAC

Connectivity	
Phase	
Current / Amperage Rating	

Screw Terminals	
Single Phase	
15 A	

Dimensions

Length	2.31 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	2.08 in
Width	2.31 in
Dimensions	2.31 in x 2.31 in x 2.08 in

General

Color	Metallic
Specifications	• Blades/Contacts - Brass • Drive Screws - Steel, zinc plated • Flange - Stainless steel • Grounding Screw - Brass • Terminal Retainer - Clear polycarbonate • Terminal Screws - Brass • UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
Listings	

UPC	783585237022
Material - Mounting Hardware	Screw Mounting
Item Type	15A Corrosion Resistant Flanged Receptacle

Material	Stainless Steel
----------	-----------------

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)



A Hubbell brand