

Locking Devices, Twist-Lock®, Marine Grade, Male Plug, 15A 277V AC, 2-Pole 3-Wire Grounding, L7-15P, Screw Terminal, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL47CM70C](#)

Locking Devices, Twist-Lock®, Marine Grade, Male Plug, 15A 277V AC, 2-Pole 3-Wire Grounding, L7-15P, Screw Terminal, Yellow

Features

- Individually molded face for each blade configuration
- Roomy wiring chamber provides ample space for wiring
- Ribbed nylon housing provides a secure grip that's impact and chemical resistant

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L7-15P
Industry Standard(s)	• Listed to UL 498 • Fed.Spec. W-C-596 • Certified to CSA C22.2 No.42

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole
Cable Range	0.230 - 0.720 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current



Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.53 in
Display Size	Standard Sized
Weight	0.20 lb.
Height	1.97 in
Width	1.53 in
Dimensions	1.53 in x 1.53 in x 1.97 in

General

Color	Yellow
Cord Range Specifications	0.325"-0.655"(8.3-16.6) • Assembly Screws - Stainless Steel • Blades - Nickel Plated Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #8-32 Bronze (Phillips / Slotted / Robertson)
UPC	783585160900
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	15A Corrosion Resistant Insulgrip® Plug
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French\]](#)



A Hubbell brand