

Straight Blade Devices, Tamper Resistant
Duplex Receptacle, Industrial Grade, 15A
125V, 2-Pole 3-Wire Grounding, 5-15R, Red

By Hubbell Wiring Device-Kellems
Catalog # [HBL5262RTR](#)

Straight Blade Devices, Tamper Resistant Duplex Receptacle,
Industrial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Red

Features

- Patented TR design eliminates plug-in difficulty and TR complaints
- Fed-Spec UL listing insures proven performance in demanding applications
- Brass mounting strap and Triple Wipe contacts
- High impact resistant face with circuit I.D. marking area
- Complies with National Electrical Code (NEC®) requirements for Tamper Resistant receptacles

Application

Extra Heavy Duty Specification Grade

Performance

Electrical: Current Interrupting: Certified for current interrupting at full rated current, Dielectric Voltage: Withstands 2,000V minimum, Mechanical: Terminal Accommodation: #12-10 AWG stranded or solid copper wire only. Terminal Identification: Terminals identified in accordance with UL 498 and CSA, Environmental:Flammability: UL 94V-2, Operating Temperature: Maximum continuous 75°C, minimum -40°C (w/o impact)

Specifications

EU RoHS Indicator	Contact Manufacturer
Nema Rating	5-15R
Industry Standard(s)	• CSA Certified 22.2, No. 42 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 VAC
Wattage	1875 W
Connectivity	Back and Side Wired



Current / Amperage Rating	15 A
---------------------------	------

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.2 lb.
Width	1.32 in

General

Color	Red
Style	Smooth Face
Series	Extra Heavy Duty
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - Nylon • Face - Nylon • Ground Contacts - .04 in. (.91) C688 Brass • Mounting Screws - Galvanized Steel • Mounting Strap - .047 in. Brass • Power Contacts - .032 in. (.81) C688 Brass • Terminal Screws - Plated steel • Wire Clamp - .062 in. (1.6) Nickel plated steel
UPC	783585542454
Type	Tamper-Resistant
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[French, English\]](#)



A Hubbell brand