

HUBBELL
Wiring Device-Kellems

**Straight Blade Devices, Extra Heavy Duty
Standard Duplex Receptacles for
Controlled Applications, Split Circuit, 20A,
125V, 2 Pole, 3 Wire Grounding**

By Hubbell Wiring Device-Kellems
Catalog # [HBL5362C1BLTR](#)

Straight Blade Devices,Extra Heavy Duty Standard Duplex
Receptacles for Controlled Applications , Split Circuit,20A, 125V,
2 Pole, 3 Wire Grounding,Blue



Features

- Permanently marked with universal power symbol and the word "CONTROLLED" to visually identify receptacles used in automatic energy management systems
- Patented TR design eliminates plug-in difficulty and TR complaints
- Markings can be read regardless of mounting orientation
- Complies with NEC Section 406.3, ASHRAE 90.1, and California Title 24 requirements
- Complements Hubbell's Load:Logic® control system or other available energy management system

Application

Extra Heavy Duty Specification Grade

Performance

Electrical: Current Interrupting- Certified for current interrupting at full rated current, Electrical: Dielectric Voltage- Withstands 2,000V minimum, Mechanical: Product Identification- Ratings are a permanent part of the device, Mechanical: Terminal Accommodation- #12-10 AWG stranded or solid copper wire only., Mechanical: Terminal Identification- Terminals identified in accordance with UL 498 and CSA, Environmental: Flammability- UL 94V-2, Environmental: Operating Temperature- Maximum continuous 75°C, minimum -40°C (w/o impact)

Specifications

Nema Rating	5-20R
Industry Standard(s)	UL Listed to UL498 File No. E2186Certified to CSA, C22.2, No. 42 File 285Fed. Spec. W-C-596NEMA® WD-6 Compliant
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG

Current

Amperage Rating	20 A
Voltage Rating	125 V
Voltage Rating Description	125 V
Connectivity	Back and Side Wired Screw Terminals
Dielectric Strength	Withstands 2,000V minimum
Current / Amperage Rating	20 A

Dimensions

Weight	0.2 lb.
Display Size	Standard Sized Product

General

Specifications	• Face: Nylon • Base: PBT • By-Pass Power Contacts : .036 in. (.9) Brass • Ground Contacts: .031 in. (.8) Brass • Clamping Plate: Plated steel:Mounting Strap: Brass • Automatic Self-grounding Staple: Stainless steel • Mounting Screws: Zinc plated steel
Color	Blue
Style	Finder Face, Duplex Receptacle
UPC	783585583853
Type	Tamper-Resistant
Series	Controlled

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)

