

EdgeConnect™ Series, Duplex Receptacle,
Industrial Grade, Weather Resistant, 2-Pole
3-Wire, 20A 125V, 5-20R, Screwless Terminal,
Ivory

By Hubbell Wiring Device-Kellems
Catalog # [HBL5362STIWR](#)

Straight Blade Devices, EdgeConnect™ , Duplex Receptacle, Industrial Grade, Weather Resistant, 2-Pole 3-Wire, 20A 125V, 5-20R, Screwless Terminal, Ivory

Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Triple and Double Wipe Contacts
- Easy access split circuit tab

Specifications

Nema Rating	5-20R
Industry Standard(s)	• UL Listed to UL498 File No. E2186 • Certified to CSA 22.2 • No. 42 File 285, Fed. Spec. W-C-596, NEMA® WD-6 Compliant • UL 94 V-2

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#14 (Solid and Stranded) - #10 (Stranded) Copper Wire Only

Current

Interrupt Rating	Certified for current interrupting at full rated current A
Voltage Rating	125 V
Dielectric Strength	Withstands 2,000V minimum
Current / Amperage Rating	20 A



Dimensions

Weight	0.25 lb.
Size	3.28x1.58x1.38

General

Color	Ivory
Style	Finder Groove Face
Listings	Terminals Identified in Accordance with UL 498 and CSA
UPC	783585729312
Type	Weather Resistant
Item Type	Receptacle
Material	Thermoplastic/C
Series	EdgeConnect™ Series

Logistics

Pallet Quantity	3200
Carton Quantity	10

Operational

Temperature Rating	• Maximum continuous 75°C • minimum -40°C (w/o impact)
--------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)