

Adapter, Marine, Molded, Straight Blade, 30A 125V, 2-Pole 3-Wire Grounding Female to 50A 125/250V, 3-Pole 4-Wire Grounding Locking Male

By Hubbell Wiring Device-Kellems
Catalog # [HBL61CM71](#)

Marine Adapter Molded, Straight Blade 30A Female to 50A Locking Male

Features

- Marine
- Molded
- Straight Blade
- 30A 125V

Application

Straight Adapter

Performance

Environmental - Moisture Resistance - IP55 Suitability

Specifications

Standards - RoHS Compliance CM
Status

Configuration

Number Of Pins Male- 50A 125/250V Twist-Lock®

Current

Amperage Rating 30 A
Current Rating 30 A
Voltage Rating 125/250 VAC
Wattage 7500 W
Current / Amperage Rating 30 A

Dimensions

Weight 3.15 lb.

General

Color	Yellow
OEM Brand Name	Hubbell Wiring Device-Kellems
Specifications	• Adapter Style - Straight (Pig Tail) • Female End Rating - 30A 125V, 2P3W Twist-Lock® • Male End Rating - 50A 125/250V, 3P4W Twist-Lock® • Poles and Wires - 2 Pole, 3 Wire Grounding • Product Type - Adapters
UPC	783585808680
Receptacle Type	Female- 30A 125V Twist-Lock®
Insulation	Insulated Body
Item Type	Adapters
Material	Composite

Logistics

Pallet Quantity	126
Carton Quantity	1

Operational

Operating Temperature	Max Continuous- 75 Degrees C, Minimum- -40 Without Impact
-----------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)

