

Straight Blade Devices, Display Type
Receptacle, Single, Floor Box for Wood
Floors, 15A 125V, 2P 3W, Brass

By Hubbell Wiring Device-Kellems
Catalog # [HBL6236](#)

Straight Blade Devices, Display Type Receptacle, Single, Floor
Box for Wood Floors, 15A 125V, 2P 3W, Brass

Features

- Display Type Receptacle
- Single
- Floor Box for Wood Floors
- 15A 125V

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94 V-2 or better, Environmental - Operating Temperatures -
Maximum continuous 75°C, minimum -40°C (w/o impact),
Mechanical - Product Identification - Ratings are a permanent
part of the device, Mechanical - Terminal Accommodation - #14-
#10 AWG copper stranded or solid conductor only, Mechanical -
Terminal Identification - Terminals identified in accordance with
UL 498 and CSA

Specifications

EU RoHS Indicator	No
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • NEMA® WD-6 Compliant • UL Listed to UL498 File E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
-----------------	------



Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Connectivity	Side Wired Only
Current / Amperage Rating	15 A

Dimensions

Length	4.53 in
Weight	1.35 lb.
Height	1.97 in
Width	2.78 in
Dimensions	4.53 in x 2.78 in x 1.97 in

General

Color	Brass
Specifications	• Base - Phenolic • Face - Phenolic • Power Contacts - .032" (.81)
UPC	Brass 783585809946

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)