

Adapter, Marine Adapter, Molded "Y", 2) 50A 125V Locking Female 2-Pole 3-Wire Grounding to 50A 125/250V, Locking Male 3-Pole 4-Wire Grounding, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL64CM55](#)

Marine Adapter, Molded "Y", Two 50A Locking Female to 50A Locking Male

Features

- Molded "Y"
- 2) 50A 125V Locking Female 2-Pole 3-Wire Grounding to 50A 125/250V
- Locking Male 3-Pole 4-Wire Grounding

Application

"Y" Adapter

Performance

Environmental - Moisture Resistance - IP55 Suitability (Connectors)

Configuration

Number Of PinsMale- 50A 125/250V Twist-Lock®

Current

Amperage Rating50 A
Current Rating50 A
Voltage Rating125/250 VAC
Wattage12500 W
Current / Amperage Rating50 A

Dimensions

Weight8.85 lb.

General

ColorYellow



OEM Brand Name
Specifications

Hubbell Wiring Device-Kellems

- Adapter Style - Y Adapter
- Female End Rating - 50A 125V, 2P3W Twist-Lock®
- Male End Rating - 50A 125/250V, 3P4W Twist-Lock®
- Poles and Wires - Female Side- 2P3W Grounding, Male Side 3P4W Grounding
- Product Type - Adapters

783585808789
Female- 50A 125V Twist-Lock®
Insulated Body
Adapters
Composite

UPC
Receptacle Type
Insulation
Item Type
Material

Logistics

Carton Quantity1

Operational

Operating TemperatureMax Continuous- 75 Degrees C,
Minimum- -40 Without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)