

Watertight Devices, Twist-Lock® Duplex
Receptacle with Lift Cover, 15A, 125VAC, 2
Pole, 3 Wire, Thermoplastic elastomer,
NEMA L5-15R, Yellow.

By Hubbell Wiring Device-Kellems
Catalog # [HBL65W47D](#)

WATERTIGHT 15A/125V, L5-15 DUPLX REC

Features

- Impact resistant PBT lid, cover plate, and receptacle body
- Thermoplastic elastomer seal
- Stainless steel hardware and corrosion-resistant connection points

Performance

Electrical - Current Interrupting - Rated for current interruption per UL498, Electrical - Dielectric Voltage - 2500V AC, Electrical - Max Working Voltage - As marked, Electrical - Temperature Rise - 30°C max per UL498 at rated current, Environmental - UV resistance - All exposed materials are UV stabilized, Environmental - Moisture Resistance - UL Listed 4, 4X, 12, 6, 6P, Environmental - Operating Temperatures - -40°C (without impact) to +60°C continuous

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L5-15R
Industry Standard(s)	• IP69K In Use • Meets NEMA WD-1, WD-6 And ANSI Standards

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Voltage Rating	125 V
Current / Amperage Rating	15 A

General

Color	Yellow
UPC	783585528748
Type	Duplex Receptacle
Item Type	15A Watertight Twist-Lock® Duplex Receptacle

Logistics

Carton Quantity	5
-----------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)

