HUBBELL
Wiring Device-Kellems

Watertight Devices, Twist-Lock® Receptacle with Lift Cover, 30A, 3 Phase WYE 120/208V AC, 4 Pole, 5 Wire, Thermoplastic elastomer, NEMA L21-30R

By Hubbell Wiring Device-Kellems
Catalog # HBL69W81

WATERTIGHT RECEP, 30A 120/208V, L21-30

Features

- Impact resistant PBT lid, cover plate, and receptacle body
- Thermoplastic elastomer seal
- Stainless steel hardware and corrosion-resistant connection points

Performance

Electrical - Current Interrupting - Rated for current interruption per UL498, Electrical - Dielectric Voltage - 2500V AC, Electrical - Max Working Voltage - As marked, Electrical - Temperature Rise - 30°C max per UL498 at rated current, Environmental - UV resistance - All exposed materials are UV stabilized, Environmental - Moisture Resistance - UL Listed 4, 4X, 12, 6, 6P, Environmental - Operating Temperatures - -40°C (without impact) to +60°C continuous

Specifications

EU RoHS Indicator	Contact Manufacturer
Nema Rating	L21-30R
Industry Standard(s)	• IP69K In Use • Meets NEMA WD-1, WD-6 And ANSI Standards

Conductor

Number Of Wires	5-Wire
Wire Size	#18 AWG to #8 AWG
Number Of Poles	4-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	3-Phase Y 120/208 VAC
Voltage Rating	3-Phase Y 120/208 VAC
Current / Amperage Rating	30 A

Dimensions

Length	4.56 in
Height	2.92 in
Width	3.10 in
Dimensions	4.56 in x 3.10 in x 2.92 in

General

Color	Yellow
UPC	783585433318
Type	Receptacle
Item Type	30A Watertight Twist-Lock® Receptacle

Logistics

Carton Quantity	5

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved