

HUBBELL
Wiring Device-Kellems

**Locking Devices, Midget Twist-Lock®,
Industrial, Male Plug, 15A 125/250V AC, 3-
Pole 3-Wire Non Grounding, NEMA ML-3P,
Screw Terminal, Black, Angled.**

By Hubbell Wiring Device-Kellems
Catalog # [HBL7432](#)

Locking Devices, Midget Twist-Lock®, Industrial, Male Plug, 15A
125/250V AC, 3-Pole 3-Wire Non Grounding, NEMA ML-3P, Screw
Terminal, Black, Angled.



Features

- Abuse resistant nylon housing
- Phenolic body for high heat resistance
- Angled body design for low profile in tight spaces
- Totally insulated body adds extra measure of safety

Application

Industrial/Commercial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #18 AWG - #14 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	ML-3P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #14 AWG
Number Of Poles	3-Pole
Cable Range	0.335 - 0.421 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current

Amperage Rating	15 A
-----------------	------



A Hubbell brand

Voltage Rating Description	125/250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125/250 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.68 in
Display Size	Midget Locking
Weight	0.05 lb.
Height	1.32 in
Width	1.17 in
Dimensions	1.68 in x 1.17 in x 1.32 in

General

Color	Black
Cord Range	0.335"-0.421"(8.5-10.7)
Specifications	• Blade Holder - Phenolic • Blades - Brass • Housing - Nylon • Terminal Clamp - Nylon • Terminal Screws - #5-40 Brass
UPC	783585237190
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	15A Midget Twist-Lock® Plug
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)