

Locking Devices, Twist-Lock®, Accessories,  
Hull Inlet Cord Clamp, Nickel Plated Brass

By Hubbell Wiring Device-Kellems  
Catalog # [HBL77CM67](#)

Locking Devices, Twist-Lock®, Accessories, Hull Inlet Cord Clamp,  
Nickel Plated Brass

Features

- Hull Inlet Cord Clamp
- Nickel Plated Brass

Application

For 50A Inlets

Specifications

|                      |           |
|----------------------|-----------|
| Industry Standard(s) | UL Listed |
| EU RoHS Indicator    | No        |

Current

|                     |                             |
|---------------------|-----------------------------|
| Connectivity        | Pressure Terminal Screws    |
| Dielectric Strength | Withstands 3000V Minimum in |

General

|                |                                                                                                                                                         |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Specifications | <ul style="list-style-type: none"><li>• Clamp range - .44 - 1.14 in. (11.1 - 29.0)</li><li>• Marine Accessory Type - Cord Clamp for 50A plugs</li></ul> |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|



|                              |                                                                                                                              |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------|
|                              | and Connectors                                                                                                               |
|                              | <ul style="list-style-type: none"><li>• Material - Nickel plated brass</li><li>• Product Type - Marine Accessories</li></ul> |
| Color                        | Metallic                                                                                                                     |
| UPC                          | 783585808840                                                                                                                 |
| Material - Mounting Hardware | Screw Mounting                                                                                                               |
| Material                     | Thermoplastic                                                                                                                |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Operational

|                    |                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Temperature Rating | <ul style="list-style-type: none"><li>• Maximum Continuous: 75° C</li><li>• Minimum Continuous: -40° C w/o impact</li></ul> |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------|

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)