

Straight Blade Devices, Female Connector Body, Valise Series, Hospital Grade, Straight, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, White, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL8119V](#)

Straight Blade Devices, Female Connector Body, Valise Series, Hospital Grade, Straight, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, White, Single Pack

Features

- Hinged one piece body design for easy assembly
- Powerful, offsetting cord grips clamp on individual conductors

Application

Hospital Grade

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2000V AC minimum, Environmental - Flammability - UL 94 HB, Environmental - IP Suitability - IP20, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #16 to #12 AWG, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #12 AWG
Number Of Poles	2-Pole
Conductor Range	#14 AWG to #12 AWG

Current

Amperage Rating	15 A
-----------------	------



Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Connectivity	Screw Terminals
Current / Amperage Rating	15 A

Dimensions

Length	2.63 in
Display Size	Standard
Weight	0.1 lb.
Height	1.13 in
Width	1.25 in
Dimensions	2.63 in x 1.25 in x 1.13 in

General

Color	White
Cord Range	0.300"-0.660" (7.6-16.8)
Specifications	• Assembly Screws - Plated Steel • Blades - Brass • Cable Inserts - PPO • Housing - Nylon
UPC	783585015798
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	Valise Connector
Material	Nylon

Logistics

Pallet Quantity	8400
Carton Quantity	10

Operational

Temperature Rating	Max Continuous- 75 Degrees C, Minimum- -40 Without Impact
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- Catalog [English]
 - Catalog Page [English]
 - Catalog Page [English]
-

