

EdgeConnect™ Series, Duplex Receptacle,
20A 125V, 5-20R, Screwless Terminal, Brown

By Hubbell Wiring Device-Kellems
Catalog # [HBL8300ST](#)

Straight Blade Devices, EdgeConnect™, Duplex Receptacle, Hospital
Grade, 2-Pole 3-Wire, 20A 125V, 5-20R, Screwless Terminal, Brown

Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Triple and Double Wipe Contacts
- Easy access split circuit tab

Application

Heavy Duty

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Nema Rating	5-20R
Industry Standard(s)	• UL Listed to UL498 File No. E2186 • Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. W-C-596,NEMA® WD-6 Compliant

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 V



Phase	Single
Current / Amperage Rating	20 A
Dimensions	
Weight	0.25 lb.
Size	Standard Sized Product

General

Color	Brown
Style	Finder Groove Face
Series	EdgeConnect™ Series
Mounting Type	Screw Mount
UPC	783585687384
Type	Hospital Grade
Item Type	Receptacle
Material	Thermoplastic/C

Logistics

Pallet Quantity	3200
Carton Quantity	10

Operational

Temperature Rating	• Maximum continuous 75°C • minimum -40°C (w/o impact)
--------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)