

Disconnect Switches, Non Fused, Hazardous Location, 100A 600V AC, 3-Pole with Aux Contact

Por Hubbell Wiring Device-Kellems
No de catálogo [HBLB7NFD21AA](#)

Disconnect Switches, Non Fused, Hazardous Location, 100A 600V AC, 3-Pole with Aux Contact

Características

- Copper-free aluminum construction to prevent corrosion
- Compact NEMA 4X enclosure and footprint allows easy installation
- Lockable handle to meet OSHA Lockout/Tagout regulations

Especificaciones

Industry Standard(s) UL98 Certified

Clasificaciones eléctricas

Amperage Rating	100 A
Current / Amperage Rating	100 A
Current Rating	100 A

Dimensiones

Height	7.81 in
Width	8.13 in
Length	13.06 in
Dimensions	13.06 in x 8.13 in x 7.81 in

General



Specifications

- Conduit Sizes - 1½ NPT
- Cover Bolts - Stainless Steel
- Finish - Grey Powder Polyester painted exterior
- O-Ring Gasket - Silicone
- Terminal Wire Size - #8-1

Color	Gray
Style	Unfused
UPC	783585242644
Type	Switch with Aux Contact
Item Type	Unfused Disconnect Switch with Auxiliary Contact
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	Disconnect Switch

Operacional

Horsepower - Maximum	50
----------------------	----

Documentación del producto

[Catalog \[English\]](#)