

Industrial Grade, Motor Disconnect, Unfused
Switch, Non-Metallic Sloped Version
Replacement Cover for 100A With Jog -
HBLDS100 and HBLDS100T Series

By Hubbell Wiring Device-Kellems
Catalog # [HBLDS100RCJ](#)

Industrial Grade, Motor Disconnect, Unfused Switch, Non-Metallic Sloped
Replacement Cover for 100A With Jog, HBLDS100 and HBLDS100T
Series

Features

- Constructed from corrosion and impact resistant UV stabilized non-metallic material
- Factory installed Hold, Off, Auto jog switch for increased safety and point of use communication to PLC
- IP69k and Type 4X,12K water ingress protection and Certified by NSF for hygiene in food processing applications
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Product rating are permanently laser-marked and will not wash off
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Factory installed Hold, Off, Auto jog switch for increased safety and point of use communication to PLC

Application

Heavy Duty Industrial and/or Washdown

Specifications

Industry Standard(s)	cULus Listed
Environmental Conditions	Indoor and Outdoor

Dimensions

Weight	1.2 lb.
--------	---------

General



Specifications

Color	Gray
Style	Replacement Cover
Ingress Protection	IP69k, NEMA Type 4X, 12
UPC	783585763422
Type	Accessories
Material - Mounting Hardware	Stainless Steel Screw Mounting
Enclosure Type	IP69k and UL Type 4X, 12
Series	Non-Fused

Logistics

Carton Quantity	1
-----------------	---

Operational

Operating Cycles	10,000 Cycles Minimum
Operating Temperature	Without Impact Maximum continuous 75°C and minimum -40 °C

Product Assets

- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)