

Straight Blade Devices, Receptacles,
Duplex, Commercial/Decorator Grade,
Isolated Ground, 2-Pole 3-Wire Grounding,
20A 125V, 5-20R, Gray, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # IG2162GY

Straight Blade Devices, Receptacles, Duplex,
Commercial/Decorator Grade, Isolated Ground, 2-Pole 3-Wire
Grounding, 20A 125V, 5-20R, Gray, Single Pack

Features

- Triangle marking on face indicates isolated ground
- Aesthetic Style Line® decorator design
- Triple wipe contacts

Application

Heavy Duty Style Line Decorator Duplex

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - Top: UL 94V-2, Base: UL 94V-0, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #12-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. WC596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	20 A
Voltage Rating	125 V
Wattage	2500 W
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	1.03 in
Width	1.36 in
Dimensions	3.28 in x 1.36 in x 1.03 in

General

Color	Gray
Style	Style Line Decorator
Series	Heavy Duty
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - PBT • Contacts - Brass • Face - Nylon • Ground Contact - .031 in. (.8) Brass • Mounting Strap - .040 in. (1) Galvanized steel • Terminal Screws - Brass • Wire Clamp - Plated brass
UPC	783585845166
Type	Standard Duplex
Material - Mounting Hardware	Screw Mounting
Item Type	Style Line Decorator Duplex
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand