

Straight Blade Devices, Receptacles,  
Duplex, Commercial Grade, Isolated  
Ground, 2-Pole 3-Wire Grounding, 15A  
125V, 5-15R, Ivory, Single Pack.

By Hubbell Wiring Device-Kellems  
Catalog # [IG5252I](#)

Straight Blade Duplex Receptacle Isolated Ground 15A

Features

- Triangle marking on face indicates isolated ground
- Slender/compact design
- Smooth Face

Application

Hubbell-Pro Heavy Duty Specification Grade

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-2, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

|                          |                                                                                                                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means                                                                                                                                                  |
| EU RoHS Indicator        | Yes                                                                                                                                                                                              |
| Nema Rating              | 5-15R                                                                                                                                                                                            |
| Industry Standard(s)     | <ul style="list-style-type: none"><li>• Certified to CSA 22.2, No. 42 File 285</li><li>• Fed. Spec. W-C-596</li><li>• NEMA® WD-6 Compliant</li><li>• UL Listed to UL498 File No. E2186</li></ul> |

Conductor

|                 |                    |
|-----------------|--------------------|
| Number Of Wires | 3-Wire             |
| Wire Size       | #14 AWG to #10 AWG |
| Number Of Poles | 2-Pole             |

Current

|                            |                           |
|----------------------------|---------------------------|
| Amperage Rating            | 15 A                      |
| Voltage Rating Description | 125 V                     |
| Dielectric Strength        | Withstands 2,000V minimum |
| Current Rating             | 15 A                      |
| Voltage Rating             | 125 V                     |



|                           |                                     |
|---------------------------|-------------------------------------|
| Wattage                   | 1875 W                              |
| Connectivity              | Back and Side Wired Screw Terminals |
| Phase                     | Single Phase                        |
| Current / Amperage Rating | 15 A                                |

Dimensions

|              |                             |
|--------------|-----------------------------|
| Length       | 3.28 in                     |
| Display Size | Standard Sized Product      |
| Weight       | 0.15 lb.                    |
| Height       | 1.07 in                     |
| Width        | 1.57 in                     |
| Dimensions   | 3.28 in x 1.57 in x 1.07 in |

General

|                              |                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color                        | Ivory                                                                                                                                                                                                                                                                                                                                                                                                   |
| Style                        | Smooth Face                                                                                                                                                                                                                                                                                                                                                                                             |
| Series                       | Hubbell-PRO                                                                                                                                                                                                                                                                                                                                                                                             |
| Specifications               | <ul style="list-style-type: none"><li>• Automatic Self-grounding Clip - Stainless steel</li><li>• Base - Nylon</li><li>• Clamp - Nickel plated steel</li><li>• Face - Nylon</li><li>• Ground Contacts - .031" (.8) Brass</li><li>• Mounting Screws - Stainless Steel</li><li>• Mounting Strap - Galvanized steel</li><li>• Power Contact - .031" (.8) Brass</li><li>• Terminal Screws - Brass</li></ul> |
| UPC                          | 783585146720                                                                                                                                                                                                                                                                                                                                                                                            |
| Type                         | Isolated Ground                                                                                                                                                                                                                                                                                                                                                                                         |
| Material - Mounting Hardware | Screw Mounting                                                                                                                                                                                                                                                                                                                                                                                          |
| Item Type                    | Traditional Duplex                                                                                                                                                                                                                                                                                                                                                                                      |
| Material                     | Nylon                                                                                                                                                                                                                                                                                                                                                                                                   |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
|-----------------------|----------------------------------------------------------|

Horsepower - Maximum0.5

Product Assets

- Catalog [English]
- Catalog Page [English]
- Catalog Page [English]
- Installation Manual [Spanish, French, English]



A Hubbell brand