

M3R002SG000

By Hubbell Wiring Device-Kellems
Catalog # [M3R002SG000](#)

3R PSDA, 2-Gang, Switched, Ground Fault



Features

- Device identification marking
- LINKOSITY® connection
- No Power pass thru option

Application

No Switch, 2) 20A 125V Spec Grade Duplex

Performance

Electrical - Amperage - Up to 30A, Electrical - Voltage - Up to 600V, Environmental - Flammability - UL94HB Cables/UL94V-0 receptacles, Environmental - Ingress Protection - IP66 Suitability, Environmental - Moisture Resistance - NEMA Type 1, Type 3R, Type 4X

Specifications

Industry Standard(s)	• Listed To UL2238 And UL50 • UL Listed
EU RoHS Indicator	No

Conductor

Cable Entry	Plug-In
-------------	---------

Dimensions

Height	12.5 in
Width	5.5 in
Depth	5.5 in

General

Specifications	• Device Feature - Standard • Style - 3R Lids
Color	Gray
UPC	783585905198
Material - Mounting Hardware	Screw Mounting
Enclosure Type	NEMA 3R
Item Type	Power System Distribution Assemblies
Material	Composite

Logistics

Carton Quantity	1
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)