

M3RSL1SGGF0

By Hubbell Wiring Device-Kellems
Catalog # [M3RSL1SGGF0](#)

3R PSDA, 2-Gang, Switched, Ground Fault



Features

- Device identification marking
- LINKOSITY® connection
- No Power pass thru option

Application

Switched, 2) 20A 125V Spec Grade GFCI Duplex

Performance

Electrical - Amperage - Up to 30A, Electrical - Voltage - Up to 600V, Environmental - Flammability - UL94HB Cables/UL94V-0 receptacles, Environmental - Ingress Protection - IP66 Suitability, Environmental - Moisture Resistance - NEMA Type 1, Type 3R, Type 4X

Specifications

Industry Standard(s)	• Listed To UL2238 And UL50 • UL Listed
EU RoHS Indicator	No

Conductor

Cable Entry	Plug-In
-------------	---------

Dimensions

Height	12.4 in
Width	5.1 in
Depth	5.3 in

General

Specifications	• Device Feature - Ground Fault • No. of Devices - One • Style - 3R Lids
Color	Gray
UPC	783585905181
Material - Mounting Hardware	Screw Mounting
Enclosure Type	NEMA 3R
Item Type	Power System Distribution Assemblies
Material	Composite

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)