

Kellems Wire Management, Liquidtight System, PolyTuff® 90 Degree Male Liquid-Tight Connector, 3/4", Non-Metallic, Black

By Hubbell Wiring Device-Kellems
Catalog # [P0759NBK](#)

Kellems Wire Management, Liquidtight System, PolyTuff® 90 Degree Male Liquid-Tight Connector, 3/4", Non-Metallic, Black

Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection

Application

Fittings are to be used with PolyTuff® I and PolyTuff® II

Performance

Environmental - Flammability - UL 94X-2, Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)

Specifications

- | | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none">• CSA Certified• UL Listed:UL50 Type 4X, 12 and 13 |
|----------------------|---|

Dimensions

- | | |
|---------------------------------|---------|
| Trade Size | 3/4 |
| Dimension - L Length Overall mm | 3.17 in |
| Weight | 0.1 lb. |



Height	2.29 in
Dimension - Thread Size	3/4" NPT
General	
Color	Black
Style	90°
Product Type	PolyTuff® Fittings
Specifications	• Fitting - Nylon • Lockwasher - Zinc plated steel • Sealing Ring - Elastomer
UPC	783585498805
Type	PolyTuff® Non-Metallic Liquidtight Fittings
Material	Nylon

Logistics

Pallet Quantity	4320
Carton Quantity	20

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)