

Industrial Grade, Pendant Controls, Push
Button Station, 6) Buttons- Two Speed,
Pilot Duty, 250V AC Max, Terminal Screws

By Hubbell Wiring Device-Kellems
Catalog # [PBS62](#)

Switches and Lighting Controls, Industrial Grade, Pendant
Controls, Push Button Station, 6) Buttons- Two Speed, Pilot Duty,
250V AC Max, Terminal Screws, Yellow



Features

- 6 button
- Two speed

Performance

Environmental - , Operating Temperatures - Max Continuous- 75
° C, Minimum -40° w/o Impact

Specifications

Environmental Conditions	Indoor and Outdoor
EU RoHS Indicator	No
Nema Rating	NEMA 3R
Industry Standard(s)	CSA Certified

Configuration

Contact Configuration	Momentary
-----------------------	-----------

Current

Amperage Rating	6 A
Connectivity	Terminal Screws
Phase	Single Phase
Contact Rating	Pilot Duty Only

Dimensions

Length	3.25 in
Display Size	Full Sized

Weight	7.8 lb.
Width	4.38 in

General

Style	Six Button
Ingress Protection	IP44
Enclosure Type	NEMA 3R
Series	Heavy Duty Series
UPC	783585610627
Type	Two Speed
Material - Mounting Hardware	Cable Mounted

Logistics

Carton Quantity	1
-----------------	---

Operational

Actuator	Push Buttons
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Indicator(s) Type	None

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)