

Complete Unit With 20A Duplex, (2) 1/2" Diameter Holes for Low Voltage Wiring, Black

By Hubbell Wiring Device-Kellems
Catalog # [PT7FSDBLA](#)

Complete Unit With 20A Duplex, (2) 1/2" Diameter Holes for Low Voltage Wiring, Black

Features

- Complete 3" Fire-Rated Poke-Through
- Prewired 20A Duplex Receptacle
- (2) 1/2" Diameter Holes for Low Voltage Wiring
- Non-metallic Cover with Painted Aluminum Flange
- Includes Junction Box

Specifications

EU RoHS Indicator	No
Industry Standard(s)	• cULus Listed • Meets ADA Standards • UL 514A Listed

Configuration

Number Of Outlets	(1) 20A Duplex Receptacle and (2) 1/2" Diameter Holes for Low Voltage Wiring
-------------------	--

General



Application - For Use On Style Specifications	Carpet FRPT - Complete Kits • Cover Material - Thermoplastic cover with aluminum flange • Floor thickness - 2 1/4 to 7 in. (57.2 to 177.8) • Mounting - 3 in. (76.2) cored concrete diameter through hole
UPC	783585494050
Material - Mounting Hardware	Step-Down Installation

Logistics

Carton Quantity	1
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)