

Complete Unit With 20A Duplex, (2) 1/2" Diameter Holes for Low Voltage Wiring, Brass Finish

By Hubbell Wiring Device-Kellems
Catalog # [PT7FSDBR2A](#)

Complete Unit With 20A Duplex, (2) 1/2" Diameter Holes for Low Voltage Wiring, Brass Finish

Features

- Complete 3" Fire-Rated Poke-Through
- Prewired 20A Duplex Receptacle
- (2) 1/2" Diameter Holes for Low Voltage Wiring, Brass Cover and Flange
- Includes Junction Box

Specifications

- | | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none">• cULus Listed• Meets ADA Standards• UL 514A Listed |
|----------------------|---|

Configuration

- | | |
|-------------------|--|
| Knockouts | Duplex Flip Covers and (2) 1/2" Diameter Holes for Low Voltage Wiring |
| Number Of Outlets | (1) 20A Duplex Receptacle and (2) 1/2" Diameter Holes for Low Voltage Wiring |

Dimensions

Weight4.95 lb.

General

- | | |
|--------------------------------|---|
| Specifications | <ul style="list-style-type: none">• Cover Material - Brass cover and flange• Floor thickness - 2 1/4 to 7 in. (57.2 to 177.8)• Mounting - 3 in. (76.2) cored concrete diameter through hole |
| Application - For Use On Style | Carpet |
| UPC | FRPT - Complete Kits
783585494159 |
| Material - Mounting Hardware | Step-Down Installation |
| Item Type | 3" Fire-Rated Poke Through Component |
| Finish Type | Brass |

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)

