


Non-Metallic Raceway, WallTrak1 Series,
Box, 1-Gang, Low Profile, Office White

By Hubbell Wiring Device-Kellems
Catalog # [PW1LPB](#)

Non-Metallic Raceway WallTrak1,Box, 1-Gang, Low Profile



Features

- Reduces inventory requirements
- Eliminates need to order three separate boxes
- Boxes available in low, standard and deep profiles

Performance

Environmental - Flame Rating - UL94V-0, Environmental -
Temperature Range - -25.6° to 158° F

Specifications

EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• CSA Standard C22.2 no. 62 • E118895 / E119190 • UL Standard UL 5A

Configuration

Number of Gang(s)	1-Gang
-------------------	--------

General

Color	Office White
Style	Low Profile
Series	PW1
Specifications	• Crush Resistance - 300 lbs. • Impact Resistance - 5 ft. lbs. • Material - UV Stabilized PVC
UPC	783585092119
Type	Boxes
Item Type	PW1 WallTrak (Latching) Series

Logistics

Carton Quantity	5
-----------------	---

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)