

Temporary Power, Spider Box, 30A 125/250V,
3-Pole 4-Wire Grounding, Locking
Receptacles, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [SDTL1A](#)

Temporary Power, Spider Box, 30A 125/250V, 3-Pole 4-Wire Grounding,
Locking Receptacles, Yellow

Features

- Spider Box
- 30A 125/250V
- 3-Pole 4-Wire Grounding
- Locking Receptacles

Application

Heavy Duty Portable

Specifications

Nema Rating6) L5-20R, 1) L15-30R
Environmental ConditionsIndoor and Outdoor

Conductor

Number Of Poles2-Pole
Number Of Wires3-Wire Grounding
Wire Size#10 AWG

Current

Amperage Rating30 A



Voltage Rating125 VAC
Wattage3750
ConnectivityPre-Wired
PhaseSingle Phase
Current / Amperage Rating30 A
Current Rating30 A

Dimensions

Display SizeStandard Sized Product

General

ColorYellow
UPC783585128702
Material - Mounting HardwareNon-Mounted, Portable
Item TypeTwist-Lock® Singles
MaterialThermoplastic
OEM Brand NameHubbell Wiring Device-Kellems

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)