



Kellems Wire Management, Cord Connectors, European Style, .18-.31", 3/8", Black

By Hubbell Wiring Device-Kellems
Catalog # [SEC38BA](#)

Kellems Wire Management, Cord Connectors, European Style, .18-.31", 3/8", Black

Features

- Low profile
- Connector body is a one-piece design with machined threads

Application

Straight Male Connector

Performance

Environmental - Flammability - UL 94V-2, Environmental - Operating Temperatures - -22°F to 225°F (-30°C to 107°C), Environmental - Protection Class - IP66 Suitability

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	IP66
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	0.18-0.31 in (4.6-7.9 mm)

Dimensions

Hub Size	3/8"
Display Size	3/8" NPT

General

Color	Black
Series	Low Profile NPT
Specifications	• Body - Nylon • Cord Diameter Inches (mm) - .18"- .31" (4.6-7.9) • Gland - Buna N • NPT HUB Size - 3/8 Inch
UPC	783585018089
Type	Connector
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Low Profile Cord Connectors
Material	Non-Metallic

Logistics

Pallet Quantity	24000
Carton Quantity	50

Operational

Temperature Rating	Minimum -22 Deg F to 225 Deg F (-30 Deg C to 107 Deg C)
--------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)