

SNAPConnect™ Straight Blade Duplex
Receptacle, Hospital Grade, 20A, Red, C1/2,
Controlled, Tamper Resistant

By Hubbell Wiring Device-Kellems
Catalog # [SNAP8300C1RTRA](#)

SNAP, HG, 20A, RED, C1/2, CONTROLLED, TR



Features

- Permanently marked with universal power symbol and the word "CONTROLLED" to visually identify receptacles used in automatic energy management systems
- Markings can be read regardless of mounting orientation
- Complies with NEC Section 406.3, ASHRAE 90.1, and California Title 24 requirements
- Complements Hubbell's Load:Logic® control system or other available energy management system

Application

SNAPConnect

Specifications

Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186, ASHRAE Energy Efficiency Standard 90.1 2010 • California Title 24 2013
Environmental Conditions	Indoor Dry Unless Protected By Additional Means

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	10 AWG-14 AWG

Current

Amperage Rating	20 A
Voltage Rating	125 V
Wattage	2500 W
Dielectric Strength	2000V minimum
Phase	Single Phase

Dimensions

Size	3.28 in x 1.64 in x 1.1 in
------	----------------------------

General

Color	Red
Style	Hospital Grade
Mounting Type	Screw Mount
UPC	783585757100
Type	Duplex Receptacle
Material	Nylon
Series	SNAPConnect® Series

Logistics

Pallet Quantity	3200
Carton Quantity	10

Operational

Temperature Rating	• Maximum continuous 75°C • minimum -40°C
--------------------	---

Product Assets

[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)