

SNAPConnect® Heavy Duty Commercial
AUTOGUARD® Self-Test GFCI Receptacle,
20A, Light Almond

By Hubbell Wiring Device-Kellems
Catalog # [SNAPGF20LA](#)

Straight Blade Devices, SNAPConnect®, AUTOGUARD®, Self-Test,
GFCI Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light
Almond

Features

- Audible SNAP, indicates solid connection
- Patented AUTOGUARD® self test technology
- Triple wipe construction
- Patented AUTOGUARD® Self-Test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired

Application

Commercial Grade

Specifications

Nema Rating	5-20R
Industry Standard(s)	UL 943 and Meets All NEC® Requirements

Conductor

Wire Size	SNAPConnect®
-----------	--------------

Current

Voltage Rating	125 VAC
Wattage	2500 W
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Height	4.12 in
--------	---------



Width	1.75 in
Length	1.48 in
Size	4.12 in x 1.75 in x 1.48 in
Dimensions	1.48 in x 1.75 in x 4.12 in

General

Specifications	• Base - Nylon • Face - Nylon • Contacts - Brass • Mounting Screws - Stainless Steel • Mounting Strap - Galvanized Steel • Power Contacts - Brass
Color	Light Almond
UPC	783585746425
Type	Standard
Item Type	Style Line GFCI Receptacle
Material	Nylon
Series	Heavy Duty

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)