HUBBELL
Wiring Device-Kellems

SNAPConnect® Heavy Duty Commercial Tamper-Resistant/Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 20A, Brown

By Hubbell Wiring Device-Kellems
Catalog # SNAPGFTW20

Straight Blade Devices, SNAPConnect®, Weather and Tamper-Resistant, AUTOGUARD®, Self-Test, GFCI Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Brown

Features

- Audible SNAP, indicates solid connection
- Patented shutter design for tamper-resistant protection
- Meets NEC requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® Self-Test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired

Application

Commercial Grade

Specifications

Nema Rating	5-20R
Industry Standard(s)	UL 943 and Meets All NEC® Requirements
Environmental Conditions	Weather Resistant

Conductor

Wire Size	SNAPConnect®

Current

Voltage Rating	125 VAC
Wattage	2500 W
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Height	4.12 in
Width	1.75 in
Length	1.48 in
Size	4.12 in x 1.75 in x 1.48 in
Dimensions	1.48 in x 1.75 in x 4.12 in

General

Specifications	• Base - Nylon • Face - Nylon • Contacts - Brass • Mounting Screws - Stainless Steel • Mounting Strap - Galvanized Steel • Power Contacts - Brass
Color	Brown
UPC	783585746166
Type	Tamper-Resistant, Weather Resistant
Item Type	Style Line GFCI Receptacle
Material	Nylon
Series	Heavy Duty

Logistics

Carton Quantity	10

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved