

USB Charger Duplex Receptacle, 15A 125V,
2-Pole 3-Wire Grounding

By Hubbell Wiring Device-Kellems
Catalog # [USB15ACGY](#)

USB Charger Duplex Receptacle, 15A 125V,2-Pole 3-Wire
Grounding



Features

- High Power 3.1 Amp, 5 Volt USB Output
- One Type A Port, One Type-C Port
- Tamper Resistant Grade Duplex Compatible
- USB Ports Rated 10,000 Cycles

Application

USB Charging/Power

Specifications

Environmental Conditions	Indoor Dry Unless Protected by Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	5-15R
Industry Standard(s)	cULus Listed to UL498, UL1310

Conductor

Number Of Wires	3-Wire
Wire Size	#14-10 AWG
Number Of Poles	2-Pole

Configuration

Mounting Method	Mounting Screws
-----------------	-----------------

Current

Amperage Rating	15 A
Dielectric Strength	1500 V Withstand

Voltage Rating	125 V
Wattage	1815 W
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Size	Standard Sized Product
------	------------------------

General

Color	Gray
Style	Style Line Decorator
Series	Hubbell-PRO
UPC	883778309953
Type	One Type A, One Type-C USB Port
Insulation	N/A
Material	Composite

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	Maximum continuous 75°C, minimum -40°C (w/o impact)
--------------------	---

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)