

Switches and Lighting Control, Control Unit,
Wireless, 16A 120/277V AC, Isolated Relay

By Hubbell Wiring Device-Kellems
Catalog # [WLC316R](#)

Switches and Lighting Control, Control Unit, Wireless, 16A 120/277V AC,
Isolated Relay

Features

- Control Units

Application

Compatible with most LED and CFL

Performance

Electrical - LED status indicator - Displays load status and provides programming feedback, Electrical - Memory - Power failure memory,Output is non-latching, Electrical - Operating voltage - 120/277V, 50/60Hz, Environment - Operating Environment - Indoor use only, Environment - Operating temperature - 32°F to 131°F (0°C to 55°C), Environment - Range - RF range is 30 ft (10m) obstructed, 60 ft (18m) line of sight, Environment - Relative humidity - 0% to 90% humidity, non-condensing, Mechanical - Maximum load - 16A general purpose. No minimum, Mechanical - Motor rating - 0.5 HP (120V AC), 1.5 HP (277V AC)

Specifications

Environmental Conditions	Indoor use only
Industry Standard(s)	UL Listed

Current

Amperage Rating	16 A
Voltage Rating Description	120/277V AC



Current Rating	16 A
Voltage Rating	120/277 VAC
Current / Amperage Rating	16 A

General

Color	White
Style	Accessories
Series	Passive Infrared
Specifications	- Isolated Relay - Normally open (NO) and normally closed (NC) dry contacts - Warranty - 1 year
UPC	783585159461
Type	Wireless - Ceiling Mount

Logistics

Carton Quantity	16
-----------------	----

Operational

Operating Temperature	32 °F to 131 °F (0 °C to 55 °C)
Humidity	0% to 90% humidity, non-condensing

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)