



Parallel Groove Connector T&B Catalog Number:

UPC Number:

PAE9999-9

Status:

78378633038

Description:

Active

Aluminum Type PAE - Parallel Groove Clamp, Extruded Type for Wire
Range Main: 1000 kcmil-397.5, ACSR 336.4-2/ AR Tap: 1000 kcmil-397.5, ACSR 336.4-2/0 AR

Features

For use on aluminum to aluminum or aluminum to copper connections with oxide inhibitor. Can be installed with live line tools.

Standard PAE clamp is supplied with Contax (-9) and galvanized steel hardware.

General

Style	Type PAE - Parallel Groove Clamp, Extruded Type
Material	Aluminum
Conductor Range ACSR Main	1000 kcmil-397.5, ACSR 336.4-2/ AR
Conductor Range ACSR Tap	1000 kcmil-397.5, ACSR 336.4-2/0 AR
Galvanized Steel Bolt Thd. Size	1/2-13 UNC
Aluminum Bolt Thd. Size	5/8-11 UNC

Dimension Information

A (inches)	2
F (inches)	3/4
H (inches)	2 13/16
L (inches)	6
W (inches)	3 1/2
Conductor Diameter Main Max.	1.152
Conductor Diameter Main Min.	0.743
Conductor Diameter Tap Max.	1.152
Conductor Diameter Tap Min.	0.743

Packaging

T&B Inner Pack	5
Package in Units	20
T&B Sold in UOM	Each
T&B Weight Per UOM	1.36 lbs. Each

Notes

Tin plating (-P) or wax dip (-6) must be specified for without oxide inhibitor-filled connectors.

Options: 7 Aluminum hardware, P Tin plating, 6 Wax dip for oxide protection.

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com