



SKU: 13/16

UPC: 0783669983319

Features & Benefits:

Description: Surecrimp Copper Soldering Lug, Conductor Size 250, 1 Hole, 3/8in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	NA
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Sight Window	No
Slotted	No
Tang End Shape	Round

Dimensions

Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	0.813
Height BX (IN)	2
Height (mm)	20.6502
Length (IN)	2.625
Length (mm)	66.675
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Tang Length (IN)	1.25
Tang Length (mm)	31.75
Tang Thickness (IN)	0.125
Tang Thickness (mm)	3.175
Tang Width (IN)	1.188
Tang Width (mm)	30.1752
Weight (LB)	0.13856544401267
Weight BX (LB)	4.3095
Width (IN)	1.188
Width BX (IN)	6.1875
Width (mm)	30.1752

Material and Finish



Conductor Material
Connector Finish
Material

Copper
Clear
Copper

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366998331

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	250 Amps
Conductor Type	Stranded

Voltage

Voltage Rating	35 kV
----------------	-------

