



SKU: 21230

UPC: 0783669420159

Features & Benefits:

Description:Heat Shrinkable Tubing, Heavy Wall, 3/4in Expanded ID, Conductor Range 1-8, 30in Tube, Black



Specs

Additional Class Attributes

Container	NA
Model	Tube
Shrink Ratio	3:1

Dimensions

Cut Length	30 in
Expanded ID (IN)	0.75
Expanded ID (mm)	19.05
Length (IN)	6
Length (mm)	152.4
Recovered ID (IN)	0.220 IN
Recovered Wall Thickness (IN)	0.090 IN

Additional Technical Specifications

Dielectric Strength	500 V/Mil
---------------------	-----------

Material and Finish

Material	Polyolefin
----------	------------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
NEMA Code	0-000-1
UPC Code	78366942015

Testing Standards

CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.2
Mil Spec #	AMS-DTL-23053/15 CLASS 1
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation



UL Control Number

8M24

UL / CULUS Specification

UL 486D Listed

UL File Number

E158587

Environment and Temperature

Flammability Rating

Flame Retardant per Mil Spec 23053/15

Minimum Shrink Temperature

120°C

Operating Temperature

-55°C to 100°C

Temperature Rating

-55°C to 100°C

Color

Color

Black

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

1 Str - 8 Str

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

1 Str - 8 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V